

MULTI-VX®
PRODUCTION EXAMPLES



SPEC 0082

12 PLASTUB® HDPE tubes Ø4x6 clear
+ 1 telecoms pair, assembled with PLASTUB®
PVC33 black sheath, stainless steel braid, PLAS-
TUB® PVC42 black sheath.



SPEC 0054

1 PLASTUB® PA tube Ø6x8 translucent
+ 1 ELASTUB® PFA tube Ø4x6 tube crystal
+ 1 ELASTUB® PFA tube Ø2x4 crystal,
assembled, PLASTUB® GR grey spiral
sheath.



SPEC 0083

2 PLASTUB® PA tubes Ø4x6
+ 3 PLASTUB® PA tubes Ø2.7x4
+ 1 PLASCORD® 33 rod Ø6, assembled
with PLASTUB® PVC33 black round sheath.

Description

Specific assemblies of different elements:
electric or traction cables, rods, reinforcing
fibres, pre-split wire, optical fibre, shielding etc.
External sheathing on demand

Applications

Transport of compressed air
and control signals

Fields

Maintenance, control, process,
instrumentation

General characteristics

- Spiral assembly of elements:
optimised bending radius
and flexibility
- Simplification and shorter
cabling installation times

Technical data

- Specific requirements: contact us

Options (contact us)



Zone Industrielle 63600 AMBERT - France
Tel. + 33 (0)4 73 82 44 36
e-mail: plastub@omerin.com

www.plastub.fr

The information given in this technical data sheet is indicative and subject to change without prior notice. As the conditions of use and the environment in which the product is used cannot be fully covered in our design work, PLASTUB shall not assume liability for any incidents in the event of inappropriate use and/or not carried out according to best practices and applicable standards.

To ensure optimal use of our products, we recommend full tests in real-life situations.

To this end, our sales department is on hand to supply samples and/or to examine the conditions of comprehensive testing in our laboratories.

© Registered trademark of PLASTUB. Drawings and photos are not contractual. Reproduction is prohibited without the prior agreement of PLASTUB.